MP-Systems RT

Performance Features:

- 1000 PSI
- Twin 8 GPM Pumps
- Designed for twin turrets
- Fixed Pressure & Infinitely
 Variable Pressure Models
- Patented Hydra-Cell Pump
- 70 Gallon Reservoir
- Feed Pump- Standard
- Dual Voltage- Standard
- PLC- Standard
- Use with Water or Oil Coolants
- 2 Port Std, 3rd Port Optional



Filtration Features Include:

- 5 Micron Filtration Std.
- Dual Filters Std.
- Quick Change Filters Std.
- Large Capacity Filters Std.
- Dirty Filter Alarm Std.
- Auto Cross Over Optional

High Pressure Coolant System

Models RTF

RTV





MP-Systems - September 2008

MP-Systems

17F Herman Drive Simsbury, CT 06070 Toll-free 877.689.1860 www.mp-systems.net

RT Specifications

Model	RTF	RTV
Fluid Type	Oil or Water Based	Oil or Water Based
Max. Pressure	Up to 1000 PSI (70 Bar)	Up to 1000 PSI (70 Bar)
Max. Flow Rate	8 GPM (30 l/m) per Outlet	8 GPM (30 l/m) per Outlet
	16 GPM (60 l/m) Max	16 GPM (60 l/m) Max
Pressure Type	Preset	Programmable
No. of Ports	2 (3rd Optional)	2 (3rd Optional)
Filtration	5μ Twin Filters	5μ Twin Filters
Main Motor HP	Twin 7.5 (10 kw)	Twin 7.5 (10 kw)
Voltage	(208/230) 480/3/60	(208/230) 480/3/60
Control Voltage	24 Volts	24 Volts
Dirty Filter Alarm	Standard	Standard
Auto Filter Cross Over	Option	Option
Feed Pump	Standard (built in)	Standard (built in)
Foot Print (L x W x H)	42" x 38" x 42.42"	42" x 38" x 42.42"
Dry Weight	700 lbs	700 lbs

Options

Option	Part Number	Description
Auto Cross Over Filters	AUTO-CR	Automatically switches filters when dirty
Line Kit	R-Line-1B	High pressure lines and fittings
Spare Filter Bag	MP2	Replacement 5 micron "O-Ring" bag
Installation	Install	Basic install to machine tool
Third Port	3rd pt	Third Port

Notes

- 1. Recommended for pumping cutting fluids up to 140 SSU @ 100° F
- 2. Confirm spare M codes (1 set per port)
- 3. Specifications are subject to change without prior notice



MP-Systems
A Division of Monster Accessories
17F Herman Drive
Simsbury, CT 06070
Toll-free 877.689.1860
www.mp-systems.net