

OTHER FEATURES:

All standard features described under REGAL STRAIGHTENERS are also included on REGAL FEEDER-STRAIGHTENERS as standard equipment... today's best buy for a all-around capacity performance and low-cost.

SAFETY GUARDING to OSHA requirements, as interpreted by Regal Industries Corporation, is furnished as standard equipment. This guarding is also available and should be installed on all Regal equipment, regardless of when it was manufactured, at modest cost. Consult factory.

INCLUDED IN BASIC PRICE OF FEEDER-STRAIGHTENERS (2 SPEED MODELS):

Standard 10 foot cord. 3 Control Switches: Switch No. 1 mounts near upstroke of press or shear, starts feeding of material; Switch No. 2, actuated by travel of material, cuts feed rate to slow speed; Switch No. 3, set at final length position, stops material feed, and simultaneously actuates press or shear. Ram upstroke starts the repeat cycle. On single speed models, Switch No. 2 is eliminated.

SPECIFICATIONS: REGAL STRAIGHTENERS & FEEDER-STRAIGHTENERS

230 SERIES

STANDARD STOCK-STRAIGHTENERS

FEEDER-STRAIGHTENERS

MODEL NUMBER	MOTOR H.P.	APPROXIMATE FLOOR SPACE (Inches)	APPROXIMATE SHIPPING WEIGHT	STOCK WIDTH (Inches)	THICKNESS CAPACITY (Mild Steel) (Inches)		APPROXIMATE SHIPPING WEIGHT	APPROXIMATE FLOOR SPACE (Inches)	MOTOR H.P.	MODEL NUMBER
					MAX.	MIN.				
30-SS-06	1-1/2	26 x 30	700	6	.150	.012	850	26 x 36	1-1/2	230-CSF-06
30-SS-12	1-1/2	26 x 30	900	12	.135	.012	1100	26 x 36	1-1/2	230-CSF-12
30-SS-18	1-1/2	26 x 30	1150	18	.104	.012	1350	26 x 36	1-1/2	230-CSF-18
30-SS-24	1-1/2	26 x 36	1400	24	.075	.012	1600	26 x 42	1-1/2	230-CSF-24
30-SS-30	1-1/2	26 x 42	1650	30	.042	.012	1850	26 x 48	1-1/2	230-CSF-30
30-SS-36	1-1/2	26 x 48	1900	36	.032	.012	2100	26 x 54	1-1/2	230-CSF-36

230 Series Machines are equipped with 7 straightening rolls, 2-1/4" diameter and 2 sets of heavy-duty, 3-1/4" diameter pinch rolls. Feed line height approximately 32".

330 SERIES

STANDARD STOCK-STRAIGHTENERS

FEEDER-STRAIGHTENERS

MODEL NUMBER	MOTOR H.P.	APPROXIMATE FLOOR SPACE (Inches)	APPROXIMATE SHIPPING WEIGHT	STOCK WIDTH (Inches)	THICKNESS CAPACITY (Mild Steel) (Inches)		APPROXIMATE SHIPPING WEIGHT	APPROXIMATE FLOOR SPACE (Inches)	MOTOR H.P.	MODEL NUMBER
					MAX.	MIN.				
0-SS-12	1-1/2	34 x 30	1250	12	.225	.018	1450	34 x 36	1-1/2	330-CSF-12
0-SS-18	1-1/2	34 x 30	1500	18	.215	.018	1700	34 x 36	1-1/2	330-CSF-18
0-SS-24	2	34 x 36	1750	24	.200	.018	1950	34 x 42	2	330-CSF-24
0-SS-30	2	34 x 42	2000	30	.135	.018	2200	34 x 48	2	330-CSF-30
0-SS-36	2	34 x 48	2250	36	.105	.018	2450	34 x 54	2	330-CSF-36
0-SS-42	2	34 x 54	2500	42	.075	.018	2700	34 x 60	2	330-CSF-42
0-SS-48	2	34 x 60	2750	48	.060	.018	2950	34 x 66	2	330-CSF-48
0-SS-60	3	34 x 72	3250	60	.030	.018	3450	34 x 78	3	330-CSF-60

330 Series Machines are equipped with 7 straightening rolls, 3-1/4" diameter and 2 sets of heavy-duty, 4-1/4" diameter pinch rolls. Feed line height approximately 36".

530 SERIES

STOCK STRAIGHTENERS or FEEDER-STRAIGHTENERS

These units are available in standard models from 24" width x 1/2" mild steel capacity to 72" x 3/16" capacity. Other width and thickness capacities are available. Consult factory, submitting all details.

REGAL